



https://europarm.fr//en/produit-18850-Skywoods-RAFALE-tactical-light

















SKU	Designation	French Law	Lumens	Battery	Mounting	MSRP
A61237	Skywoods RAFALE tactical light	Vente libre	600	CR2032	21mm rail	47.00 € incl. tax

600 Lumen tactical flashlight.

LED: CREE XPL-V6Output: High 500LM

Lighting Mode: High, StrobeDuration of use: 2 hours

Beam Distance: High? 116M
Case material: aluminum alloy

Water resistance: IP65Impact resistance: 1mBattery: 1x CR123A

■ Application Rail: Suitable for 21mm rails

■ Device dimensions: 32.6*29.5*62.5mm

■ Net weight: 74.5 g (with battery)

■ Durable Material:

• Anodized aluminum alloy shell provides exceptional durability for rugged use.

■ Versatile Lighting Modes:

■ Two lighting modes available: fixed and strobe, ensuring flexibility of use adapted to various situations.

■ High-performance LED lighting:

■ Equipped with an XPL-V6 LED, this lamp offers a stable brightness of ?3200Lux with a color temperature of 5700-7000k.

■ Battery Life:

■ The lamp offers two durations of use: 2 hours in fixed mode and 5 hours in strobe mode, ensuring reliable autonomy.

■ Compact and Portable Design:

■ Compact dimensions of 32.6 29.5 61mm and a net weight of 74.5g with battery, providing optimal portability.

■ Resistance to External Conditions:

■ Aluminum alloy housing material, waterproof to IP66 standard, shock resistant up to 1mm.

■ Non-Rechargeable Battery:

■ Powered by a CR123 alkaline battery, providing a reliable and convenient power source (non-rechargeable).

■ Ambidextrous Switch:

■ Both sides of the lamp feature an ambidextrous switch allowing easy control of the light. One press activates Steady On mode, while two quick presses activates strobe mode.

■ Compatibility with Firearms:

■ Designed to be safe and suitable for firearms with a MIL-STD-1913 (Picatinny) rail, providing wide applicability.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.