



EUROP-ARM

Depuis 1973

Lee 452-252-SWC Double Cavity

<https://europarm.fr/en/produit-21197-Lee-452-252-SWC-Double-Cavity>



SKU	Designation	French Law	Caliber	Bullet type	Diam. (")	Grains	MSRP
LE866	Lee 452-252 SWC #90356	Vente libre	.45 Auto (ACP)	Semi Wad Cutter	0.452	252	69.00 € incl. tax

Double cavity mold for .452" 252 gr SWC bullets - efficient and repeatable production.

Lee double cavity mold designed to produce Semi-Wadcutter projectiles for .45 calibers.

- **Type:** Semi-Wadcutter (SWC)
- **Diameter:** .452 inch (11.48 mm)
- **Weight:** 252 grains
- **Overall ball length (OAL):** .665 inch
- **Crimp groove ? nose distance:** .305 inch
- **Alveoli:** 2 (double cavity)
- **Sleeves:** handles included
- **Manufacturer reference:** #90356
- **Common calibers:** .45 ACP / .45 Auto Rim / .45 Colt

Recommended use

Designed for the production of .452" (252 gr) Semi-Wadcutter projectiles for reloading in .45 ACP, .45 Auto Rim and .45 Colt. This double cavity mold allows for increased output when manufacturing small batches for testing or range practice.

Design and operation

The mold has two identical cavities, allowing for the casting of two projectiles per cycle. The included handles facilitate opening/closing and handling during casting. Strict safety procedures must be followed when melting and casting lead alloys.

Dimensions and adjustments

The important dimensions influencing reloading are the **.452" diameter**, the **252-grain weight**, the **.665" OAL**, and the distance from the crimp groove to the nose (.305"). These measurements allow you to anticipate case positioning and crimping; always check the mechanical fit with your

cases and firearm before use.

Compatibility and practical advice

Compatible with the following calibers: .45 ACP, .45 Auto Rim, and .45 Colt, subject to dimensional control of your components. Use an alloy and pouring temperature appropriate for the mold (common lead-tin or lead-antimony alloys) and apply a release agent if recommended by the manufacturer. Check dimensions after cooling and deburr/remove any excess material if necessary.

- **Production:** 2 balls per cycle
- **Quality control:** measure diameter and OAL before reloading
- **Safety:** Wear protective gear, handle molten alloys with care

FAQ

■ **Q: Does this mold produce bullets suitable for .45 ACP?**

Yes, the .452" geometry and 252 gr weight correspond to profiles used in .45 ACP, .45 Auto Rim and .45 Colt - check the fit with your cases before use.

■ **Q: How many balls can be sunk per cycle?**

Two projectiles (double cavity).

■ **Q: Does the mold require specific handles?**

Handles are included with the mold; use heat-resistant gloves and follow safety instructions when pouring.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.