



EUROP-ARM

Depuis 1973

Scalarworks Kick/06 RMR 12 O'clock Mount

<https://europarm.fr/en/produit-21659-Scalarworks-Kick-06-RMR-12-O-clock-Mount>



 SCALARWORKS

NEW

SKU	Designation	French Law	Height (cm)	Weight (g)	Colors	MSRP
SW42501	bottom - 0.47"	Vente libre	1.2	19	Black	90.00 € incl. tax
SW42502	top - 1"	Vente libre	2.5	27	Black	90.00 € incl. tax

Position your red dot at 12 o'clock on your FUSE one-piece mount.

The **Scalarworks KICK/06** is a 12 o'clock mount designed to integrate a **Trijicon RMR red dot sight** above a primary optic, providing fast and perfectly aligned secondary aiming.

- **Configurations:** Low (SW3400), High (SW3420)
- **Mounting compatibility:** FUSE/02, FUSE/03, FUSE/04, FUSE/05
- **Optical compatibility:** Trijicon RMR, SRO, RCR, Holosun 407C/507C/508T series
- **Materials:** 7075-T6 Aluminum / 4140H Steel
- **Finish:** Type III Anodizing / Flash Nitride
- **Height:** SW3400: 12 mm
- **Height:** SW3420: 25 mm
- **Weight:** 19 to 27 g depending on the version
- **Origin:** United States

Box contents

- **Media:** Scalarworks® KICK/06™
- **Screws:**
 - (2) #6-32 x 0.4375" Nylon Pan Head Screw
 - (2) M4 x 0.7 nylon socket head cap screw
- **Tools :**
 - Scalarworks® T15 Torx Bit
 - Scalarworks® T20 Torx Bit

A 12-hour edit dedicated to RMR standards

The **Scalarworks KICK/06** allows you to mount a **red dot sight** above your main optic, in the **12 o'clock** position. This configuration is particularly appreciated for quickly switching between magnified sighting and reflexive target acquisition. In the field, this small detail truly makes a difference to the fluidity of use.

Two height settings for precise adjustment

Available in **low (SW3400 - 12 mm)** and **high (SW3420 - 25 mm)** versions, this mount allows you to adjust the **red dot sight** 's position to suit your ergonomics and setup. A well-chosen height immediately improves comfort and acquisition speed.

Wide compatibility with RMR optics

The **KICK/06** is designed to accommodate a wide range of **Trijicon RMR** standard optics: RM01 to RM09, **SRO** , **RCR** , as well as popular **Holosun** models such as the **HS407C** , **HS507C** , or **HE508T** . It integrates seamlessly with **Scalarworks FUSE** mounts for a consistent and robust installation.

Robust construction and high-end finish

Machined from **7075-T6 aluminum** and reinforced with **4140H steel** , this mount combines lightness and strength. **Type III Flash Nitride** anodizing ensures excellent durability. Weighing between **19 and 27 grams** , it remains discreet while being perfectly reliable.

FAQ

Is this setup compatible with all red dots?

It is compatible with Trijicon RMR standard optics and some Holosun models sharing this footprint.

Which height should I choose: low or high version?

The lower version promotes compactness, while the higher version improves visual comfort depending on your configuration.

Which mounting systems is it compatible with?

It is compatible with Scalarworks FUSE/02, FUSE/03, FUSE/04 and FUSE/05 assemblies.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.