



SKU	Designation	French Law	Height (cm)	Weight (g)	Colors	Mounting	MSRP
SW305157	height 1.57"	Vente libre	4	149	Black	21mm rail	480.00 € incl. tax
SW305170	height 1.7"	Vente libre	4.3	160	Black	21mm rail	480.00 € incl. tax

Supplied with level drive tool for leveling the optics with the mount.

The **Scalarworks FUSE/02** is a 30mm one-piece mount designed to offer rigidity, lightness and ease of installation on **Picatinny** rail, ideal for LPVO and long-range optics.

- **Ring diameter:** 30 mm
- **Rail compatibility:** MIL-STD-1913 Picatinny
- **Tilt:** 0 MOA
- **Extension compatibility:** KICK/01, KICK/06, KICK/07, KICK/08
- **Materials:** 7075-T6 Aluminum / 4140H Steel
- **Finish:** Type III Anodizing / Flash Nitride
- **Available heights:** 1.57" (40 mm) / 1.70" (43 mm)
- **Weight:** 149 to 160 g depending on the version
- **Origin:** United States

Box contents

- **Media:** Scalarworks® FUSE/02™
- **Screws:**
 - (12) #8-40 screw with nylon patch
- **Tools :**
 - Scalarworks® T15 Torx Bit
 - Scalarworks® T25 Torx Bit
 - Scalarworks® LevelDrive® Tool

A mount specifically designed for 30mm lenses

The **Scalarworks FUSE/02** is designed for **30mm** optics, particularly **LPVOs** and high-magnification telescopes. From the moment you set it up, you can feel its focus on simplicity and efficiency, with a quick and intuitive bolt-on system.

LEVEL DRIVE adjustment tool

Each mount comes with its own level drive tool. This tool is installed in the one-piece mount to ensure perfect alignment between the scope and the mount. A bubble level is not required.

Two heights for optimal adjustment

Available in **1.57" (40 mm)** and **1.70" (43 mm)** , this mount allows you to precisely adjust the sight line to suit your setup. In practice, this improves shooting comfort and target acquisition speed.

Scalable platform with 12 o'clock red dot

The **FUSE/02** allows the integration of a **secondary red dot sight** in the **12 o'clock** position using **KICK** extensions. Compatible with the **KICK/06** (RMR), **KICK/07** (ACRO), **KICK/08** (DPP/RMSc) and **KICK/01** (Dive Board Picatinny), it offers great modularity.

Robust construction and controlled weight

Made from **7075-T6 aluminum** with **4140H steel** reinforcements, this mount features **Type III** anodizing and a **Flash Nitride** treatment. Despite its robustness, it remains lightweight, weighing between **149 and 160 g** .

Extended compatibility

The **FUSE/02** is compatible with **MIL-STD-1913 Picatinny** rails and fits many platforms, including **B&T** models. It provides a reliable and durable foundation for any performance-oriented setup.

FAQ

Which height should I choose between 1.57" and 1.70"?

The 1.57" height is lower and more compact, while the 1.70" improves comfort depending on your posture and equipment.

Can a secondary red dot be added?

Yes, via the KICK/01, KICK/06, KICK/07 and KICK/08 extensions in the 12 o'clock position.

Is this assembly compatible with all rails?

It is compatible with MIL-STD-1913 Picatinny standard rails.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.