



SKU	Designation	French Law	Height (cm)	Weight (g)	Colors	Mounting	MSRP
SW305157	height 1.57"	Vente libre	4	149	Black	21mm rail	480.00 € incl. tax
SW305170	height 1.7"	Vente libre	4.3	160	Black	21mm rail	480.00 € incl. tax

## Supplied with level drive tool for leveling the optics with the mount.

The **Scalarworks FUSE/02** is a 30mm one-piece mount designed to offer rigidity, lightness and ease of installation on **Picatinny** rail, ideal for LPVO and long-range optics.

- **Ring diameter:** 30 mm
- **Rail compatibility:** MIL-STD-1913 Picatinny
- **Tilt:** 0 MOA
- **Extension compatibility:** KICK/01, KICK/06, KICK/07, KICK/08
- **Materials:** 7075-T6 Aluminum / 4140H Steel
- **Finish:** Type III Anodizing / Flash Nitride
- **Available heights:** 1.57" (40 mm) / 1.70" (43 mm)
- **Weight:** 149 to 160 g depending on the version
- **Origin:** United States

## Box contents

- **Media:** Scalarworks® FUSE/02™
- **Screws:**
  - (12) #8-40 screw with nylon patch
- **Tools :**
  - Scalarworks® T15 Torx Bit
  - Scalarworks® T25 Torx Bit
  - Scalarworks® LevelDrive® Tool

**A mount specifically designed for 30mm lenses**

The **Scalarworks FUSE/02** is designed for **30mm** optics, particularly **LPVOs** and high-magnification telescopes. From the moment you set it up, you can feel its focus on simplicity and efficiency, with a quick and intuitive bolt-on system.

### **LEVEL DRIVE adjustment tool**

Each mount comes with its own level drive tool. This tool is installed in the one-piece mount to ensure perfect alignment between the scope and the mount. A bubble level is not required.

### **Two heights for optimal adjustment**

Available in **1.57" (40 mm)** and **1.70" (43 mm)** , this mount allows you to precisely adjust the sight line to suit your setup. In practice, this improves shooting comfort and target acquisition speed.

### **Scalable platform with 12 o'clock red dot**

The **FUSE/02** allows the integration of a **secondary red dot sight** in the **12 o'clock** position using **KICK** extensions. Compatible with the **KICK/06** (RMR), **KICK/07** (ACRO), **KICK/08** (DPP/RMSc) and **KICK/01** (Dive Board Picatinny), it offers great modularity.

### **Robust construction and controlled weight**

Made from **7075-T6 aluminum** with **4140H steel** reinforcements, this mount features **Type III** anodizing and a **Flash Nitride** treatment. Despite its robustness, it remains lightweight, weighing between **149 and 160 g** .

### **Extended compatibility**

The **FUSE/02** is compatible with **MIL-STD-1913 Picatinny** rails and fits many platforms, including **B&T** models. It provides a reliable and durable foundation for any performance-oriented setup.

### **FAQ**

#### **Which height should I choose between 1.57" and 1.70"?**

The 1.57" height is lower and more compact, while the 1.70" improves comfort depending on your posture and equipment.

#### **Can a secondary red dot be added?**

Yes, via the KICK/01, KICK/06, KICK/07 and KICK/08 extensions in the 12 o'clock position.

#### **Is this assembly compatible with all rails?**

It is compatible with MIL-STD-1913 Picatinny standard rails.

*Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.*