



EUROP-ARM

Depuis 1973

Scalarworks LEAP/04 RMR QD Mount

<https://europarm.fr/en/produit-21679-Scalarworks-LEAP-04-RMR-QD-Mount>



 SCALARWORKS **NEW**

SKU	Designation	French Law	Height (cm)	Weight (g)	Colors	Mounting	MSRP
SW115157	MONTAGE SCALARWORKS LEAP04 TRIJICON RMR H. 1.57	Vente libre	4	45	Black	21mm rail	240.00 € incl. tax
SW115193		Vente libre	4.9	48	Black	21mm rail	240.00 € incl. tax

Compact QD mounting for Trijicon RMR platform.

The **Scalarworks LEAP/04** is a quick-detach mount designed for **Trijicon RMR** standard optics, offering lightness, robustness and repeatability on **Picatinny** rail.

- **Optical compatibility:** Trijicon RMR, SRO, RCR, Holosun 407C, 507C, 508
- **Rail compatibility:** MIL-STD-1913 Picatinny
- **Available heights:** 1.57" (40 mm) / 1.93" (49 mm)
- **Co-witness:** Lower-third (1.57") / PEAK/02 compatible (1.93")
- **Materials:** 7075-T6 Aluminum / 4140H Steel
- **Finish:** Type III Anodizing / Flash Nitride
- **Weight:** 45 to 48 g depending on the version
- **Origin:** United States

Box contents

- **Support:** Scalarworks® LEAP™
- **Screws:**
 - (2) #6-32x0.4375" screw with nylon patch
- **Tools :**
 - Scalarworks® T15 Torx Bit

A mount specifically designed for RMR optics

The **Scalarworks LEAP/04** is designed for optics using the **Trijicon RMR** standard and derivatives. Its design ensures stable and perfectly aligned mounting on **Picatinny** rails, suitable for modern configurations.

Two heights for personalized ergonomics

Available in **1.57" (40 mm)** and **1.93" (49 mm)** , this mount allows you to adjust the line of sight to suit your posture and equipment. In practice, this improves comfort and acquisition speed.

ClickDrive Quick-Detach System

The **ClickDrive** mechanism allows for quick, tool-free assembly and disassembly, while ensuring a reliable **return to zero** . Its compact design eliminates levers and protruding parts.

Optimized construction and maximum resistance

Machined from **7075-T6 aluminum** on six sides, the **LEAP/04** offers an excellent stiffness-to-weight ratio. Stress testing and **FEA** analysis have optimized every gram to ensure strength and durability.

Compact profile and smooth handling

With less than **7 mm** of lateral overhang, this mount remains discreet and ergonomic. No bulky levers hinder operation, improving fluidity in the field.

FAQ

Is this setup compatible with all RMR optics?

Yes, it is compatible with Trijicon RMR, SRO, RCR as well as compatible Holosun models.

What height should I choose?

1.57" for a standard configuration, 1.93" for a more upright posture and increased comfort.

Does the Quick-Detach system retain the setting?

Yes, the ClickDrive system guarantees a reliable return to zero after disassembly.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.