

**EUROP-ARM**

Depuis 1973

Rubber Buffer 9 to 28 mm - Country

<https://www.europarm.fr/en/produit-2188-Rubber-Buffer-9-to-28-mm-Country>

**COUNTRY®**

| SKU | Designation | French Law | Thickness (cm) | Colors | MSRP |
|--------|-------------|-------------|----------------|--------|-------------------|
| A50513 | 9 mm | Vente libre | 0.9 | Black | 13.00 € incl. tax |
| A50517 | 16 mm | Vente libre | 1.6 | Black | 14.00 € incl. tax |
| A50521 | 20 mm | Vente libre | 2 | Black | 15.00 € incl. tax |
| A50529 | 28 mm | Vente libre | 2.8 | Black | 19.00 € incl. tax |

Comfort and recoil absorption for rifles and shotguns, several thicknesses available.

Country recoil pad made of **shock-absorbing rubber** designed to reduce recoil and improve shoulder stability. Available in five thicknesses to suit comfort needs or desired stock length.

- **Brand:** Country
- **Material:** Soft, non-slip rubber
- **Available thicknesses:** 9 mm (A50513), 16 mm (A50517), 20 mm (A50521), 24 mm (A50525), 28 mm (A50529)
- **Attachment:** direct screwing onto a wooden or synthetic stock
- **Center distance:** 90 mm
- **Back surface:** anti-slip grid
- **Color:** matte black

Shooting comfort and absorption

Made of **shock-absorbing rubber**, this butt plate significantly reduces recoil during firing, minimizing shoulder fatigue and improving weapon control. Its thin or thick profile allows for stock length adjustment to suit the shooter's preference.

Thickness options

Available in five versions:

- **A50513 – 9 mm:** slim version, ideal for light weapons or compact shoulders
- **A50517 – 16 mm:** moderate absorption, general use hunting
- **A50521 – 20 mm:** enhanced comfort, consistent shooting

- **A50525 – 24 mm:** superior damping, high-recoil rifles
- **A50529 – 28 mm:** maximum comfort, magnum caliber or long shooting session

Easy assembly

The plate is screwed onto the stock (90 mm center-to-center distance). It can be adjusted by lightly sanding around the edges to perfectly fit the stock's profile. The non-slip checkering ensures excellent grip on the shoulder, even in wet conditions.

Interview

Clean with clean water and wipe dry after use. Avoid prolonged contact with solvents or mineral oils that may damage the rubber.

FAQ

- **Q: How do I choose the right thickness?**

Depending on the caliber and desired stock length: 9–16 mm for light calibers, 20–28 mm for powerful calibers.

- **Q: Can this plate be mounted on a synthetic stock?**

Yes, direct screwing is possible on most wooden or polymer stocks.

- **Q: Is it compatible with all shoulder weapons?**

Yes, the plate can be easily cut or sanded to fit the profile of the standard stock.

Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.