



**EUROP-ARM**

Depuis 1973

## Rubber Buffer 9 to 28 mm - Country

<https://europarm.fr/en/produit-2188-Rubber-Buffer-9-to-28-mm-Country>



**COUNTRY®**

SKU	Designation	French Law	Thickness (cm)	Colors	MSRP
A50513	9 mm	Vente libre	0.9	Black	13.00 € incl. tax
A50517	16 mm	Vente libre	1.6	Black	14.00 € incl. tax
A50525	24 mm	Vente libre	2.4	Black	24.00 € incl. tax
A50529	28 mm	Vente libre	2.8	Black	19.00 € incl. tax

### **Comfort and recoil absorption for rifles and shotguns, several thicknesses available.**

**Country** recoil pad made of **shock-absorbing rubber** designed to reduce recoil and improve shoulder stability. Available in five thicknesses to suit comfort needs or desired stock length.

- **Brand:** Country
- **Material:** Soft, non-slip rubber
- **Available thicknesses:** 9 mm (A50513), 16 mm (A50517), 20 mm (A50521), 24 mm (A50525), 28 mm (A50529)
- **Attachment:** direct screwing onto a wooden or synthetic stock
- **Center distance:** 90 mm
- **Back surface:** anti-slip grid
- **Color:** matte black

### **Shooting comfort and absorption**

Made of **shock-absorbing rubber**, this butt plate significantly reduces recoil during firing, minimizing shoulder fatigue and improving weapon control. Its thin or thick profile allows for stock length adjustment to suit the shooter's preference.

### **Thickness options**

Available in five versions:

- **A50513 - 9 mm:** slim version, ideal for light weapons or compact shoulders
- **A50517 - 16 mm:** moderate absorption, general use hunting
- **A50521 - 20 mm:** enhanced comfort, consistent shooting

- **A50525 - 24 mm:** superior damping, high-recoil rifles
- **A50529 - 28 mm:** maximum comfort, magnum caliber or long shooting session

### **Easy assembly**

The plate is screwed onto the stock (90 mm center-to-center distance). It can be adjusted by lightly sanding around the edges to perfectly fit the stock's profile. The non-slip checkering ensures excellent grip on the shoulder, even in wet conditions.

### **Interview**

Clean with clean water and wipe dry after use. Avoid prolonged contact with solvents or mineral oils that may damage the rubber.

### **FAQ**

- **Q: How do I choose the right thickness?**

Depending on the caliber and desired stock length: 9-16 mm for light calibers, 20-28 mm for powerful calibers.

- **Q: Can this plate be mounted on a synthetic stock?**

Yes, direct screwing is possible on most wooden or polymer stocks.

- **Q: Is it compatible with all shoulder weapons?**

Yes, the plate can be easily cut or sanded to fit the profile of the standard stock.

*Les prix de vente conseillés sont mentionnés à titre indicatif. Les armuriers sont libres de vendre au prix qu'ils souhaitent. Textes et photos non contractuels, sujet à modification.*